

# Facilities List Fabrication

### Plasma/Oxy Cutting Systems

#### **Messer MG Titan II Cutting Machine**

2 MG Titan II Thermal Cutting Machines on a common rail 4 ALFA Oxyfuel torches per Cutting Machine 1 HyPerformance Plasma HPR260 torch per Cutting Machine 10' x 80' self cleaning downdraft cutting table

#### **Laser Cutting Systems**

#### ByStronic BySprint Pro 4020 Fiber Laser 6000 Watt

80" x 160" dual pallet tables

#### Cincinnati CL-850 Laser 5000 Watt

80" X 160" dual pallet tables

#### <u>Forming Equipment</u>

#### Carell 307HV4 Angle Roll

Capacities: Flats Hard -4" x 1"  $\phi$ 44" Flats Easy -7" x 1-38/"  $\phi$ 32" Pipe Schedule 40 -4"  $\phi$ 45" Angle Leg-in -4" x 38"  $\phi$ 50"

#### **Accurpress 548514 Accell Series Press Brake**

485 Ton Synchronized CNC Press Brake, 14' capacity with automatic back gauging and crowning systems

#### Strippit/LVD CNC Press Brake

350 Ton, 8-axis, 10' capacity

#### **Pacific Hydraulic Press Brake**

400 Ton, 16' capacity with automatic back gauging

#### **Roundo PS255 Plate Bending Roll**

double pinch type,  $10' \times 1/2''$  capacity, bar-on-edge capacity  $3'' \times 1-1/8''$ , angle capacity  $3'' \times 3/8''$ 

#### New Dimension P4.25 Roll 4' x 1/4" capacity

301 East Main Street | Black River Falls, WI 54615 | 715-284-5376 | www.dsmfg.com | sales@dsmfg.com | ISO 9001:2008 Certified



# Facilities List Machining Centers - CNC

#### **Bridge Mill**

#### **Okuma MCR-A5CII Dual Column Bridge Mill**

100" X 200" X 65" work envelope, max table weight 59,400 lbs. programmable 90 degree head, 5-side machining capability with coolant through the spindle, paired with 20,000 lb. crane

### **Horizontal Machining Centers**

Toyoda FH1250SX Twin Pallet Axis travels; x = 87", y = 63", z = 72", swing=96" Toyoda FA800 Twin Pallet Axis travels; x = 53", y = 45", z = 45", swing=63" Toyoda FH630SX Twin Pallet Axis travels; x = 39", y = 32", z = 33" Toyoda FH450S Twin Pallet Axis Travels; x = 23", y = 23", z = 23" Okuma MB-500H Axis travels; z = 30", z = 30", z = 30"

#### **Vertical Machining Center s**

**2 HAAS VF-6/50** Axis travels; x = 64", y = 28", z = 25" **2 Haas VF-5/50** Axis travels; x = 50", y = 26", z = 25" **HAAS VF-2SS** Axis travels; x = 30", y = 20", z = 20" **2 HAAS HRT310 4**<sup>th</sup> **Axis Positioners** all HAAS VMCs are 4<sup>th</sup> axis capable

#### <u>Turning – CNC</u>

**DMG Mori CTX Beta 800** Sub spindle lathe with live tools, max swing 20" max length 31.5"

**HAAS ST-40T** 55 hp CNC lathe with live tools, max swing 25.5" Max cutting length 44" Big bore through spindle capacity 4" max diameter.

#### Saw

**HYD-MECH M16A** automatic horizontal band saw 18" x 27" capacity with miter cutting 7.5 HP 60 HZ



# Facilities List Welding

#### **Welders and Positioners**

#### **Robotic Welding Systems**

**ABB/Wolf Robotics 500B** - Includes one IRB 2400L six axis robot, one IRBP 500B 5 axis positioner, and one Lincoln Powerwave 455M weld power supply. Capacity 40" x 57" x 1100 lbs.

**(3) ABB/Wolf Robotics 750B** - Includes one IRB 2400L six axis robot, one IRBP 750B 5 axis positioner, and one Lincoln Powerwave 455M weld power supply. Capacity 40" x 57" x 1650 lbs.

**ABB/Wolf Robotics 1000K** — Includes two IRB 2600-12 six axis robots, one IRBP 1000k 3 axis positioner, and two Lincoln Powerwave 455M weld power supplies. Capacity 55" x 157" x 2200 lbs

**ABB/Wolf Robotics 5000K Sky Hook** — Includes one IRB 4600-20 six axis robot mounted to a robot travel track, one 5000KG 2 axis sky hook positioner, preheat package with temperature sensing, and one Lincoln Power Wave S700 power supply.

Capacity 100" x 142" x 11,000 lbs.

#### **Manual Welding**

12 Miller pulsed 450 amp multi-process welders

43 wire feed welders from 350 to 650 amps.

Multiple weld positioners and rotators up to 10,000 lb capacity.



## **Facilities List**

## Finishing / Additional Information

#### **Paint Systems**

#### **Batch Booth Coating System**

Part capacity wet paint: 14' x 14' x 25' Part capacity powder coat: 14' x 14' x 20' Indexable conveyor with 5 ton hanging capacity, in line wash system with reclamation for cleaning and phosphatizing and dry cycle, wet paint booth with bake cycle up to 200 ° F, powder coat booth and bake oven 180° - 450° F.

#### **Powered Conveyor System**

Part capacity: 4' x 4' by 10'

Six-stage power spray wash booth with iron phosphatizing 3 spray booths, prime coat oven and topcoat oven booth with 450° capacity

1 powder booth

1466' of track and 1100 hooks rated at 300 lbs. each

#### **Shot Blasters**

**Pangborn ES-2050 Wire Mesh Belt Blaster** 48" X 36" work envelope, 8 265DD Genesis 26 1/2" 25 HP wheels, belt speeds 2 ft./min. to 20 ft./min.

**Bronco 7' Two Wheel Table Blaster** 


**Bronco 6.5 Cu Ft. Tumble Blaster** 

#### **Inspection Equipment**

**Brown & Sharpe Status 9158 DCC CMM** travels x = 900mm, y = 1500mm, z = 800mm, accurate within +/-.00035 **Faro Fusion Series portable CMM** 10' spherical measurement range Accurate within +/-.0010"

### **Material Handling/Shipping**

Various overhead cranes up to 10-ton capacity Case 621 Wheel Loader with fork attachment 8 forklifts with capacities from 5,000 lb. to 12,000 lb.



# **Facilities List**

3 1 Street | Black River Falls, WI 54615 | 715-284-5376 | www.dsmfg.com | sales@dsmfg.com | ISO 9001:2008 Certified

Manufacturing ISO 9001:2008 Certified Contract Metal Fabrication, Machining, Welding, Assembly, and Finishing